

Meet the Ultimate 5-in-1 COB HotStik™!


You won't believe your eyes when you see the intensely bright, super rich colors produced by the HotStik™ 5 COB II, 1-meter long LED baton style 5-in-1 RGBAW LED fixture! The HotStik™ 5 COB II is powered by 12x 25-watt high output RGBAW COB LEDs, and maintains all the same great features that made the original HotStik™ 5 COB such an outstanding success!

Its 5-in-1 RGBAW LED's provide a vastly increased color gamut and drastically reduced multicolored shadowing versus conventional LEDs, and programming is a snap with the HotStik™ 5 COB II's large LED control panel. And as always, we also pay plenty of attention to ergonomics and construction, and the HotStik™ 5 COB II delivers here as well, with PowerCON® compatible power in/out connectors and 3-pin DMX connectors for easy daisy-chaining of DMX and power.

With an awesome array of built-in color macros, automated programs, plus sound active mode via master/slave, the HotStik™ 5 COB II is a perfect solution for any type of accent lighting. Plus, with the improved flexibility of either 4/5/9 or 10-channel DMX modes, it will work great with any type of controller, including our own 4-channel Klimate Kontrol™, or 5 channel Kontrol™ 5 lighting controllers. Whatever the application, HotStik™ 5 COB II fixtures will deliver outstanding color reproduction in a smart, well designed linear wash package!

You can also take full advantage of Blizzard's wiCICLE® wireless DMX system without the need for external power thanks to the wiCICLE enabled DMX jacks! An innovative design provides power to the system directly from the fixture's DMX jack, meaning even fewer cords and less setup time!

Photometric Data: 60° Beam Angle LUX (Full RGBAW)



15,660 @ 1m	5,700 @ 2m	2,600 @ 3m	1,420 @ 4m	1,000 @ 5m
-------------	------------	------------	------------	------------

DISCLAIMER:

The power connector fitted to the fixture & fixture cord are designed for compatibility with products manufactured by Neutrik AG, Neutrik USA and related entities, however they are not manufactured by, affiliated with or endorsed by Neutrik AG, Neutrik USA, or any related entity. Neutrik® and powerCON® are registered trademarks of Neutrik AG.

HOTSTIK™ cob II



Main Features

- 12x 25W 5-in-1 COB LEDs, 100,000 hours
- Variable electronic strobe
- Variable electronic dimmer
- Built-in color & chase macros via DMX
- Built-in automated programs + Sound Active via M/S
- RGBAW color mixing ability in standalone mode
- Beam Angle: 60 degree
- 3-pin male input and 3-pin female output
- User selectable 4/5/9 or 10-Channel DMX modes
- Can directly power the wiCICLE® wireless system via DMX
- Flicker-free constant-current LED driver
- Easy to use LED control panel
- PowerCon™ compatible AC power In/Out connectors

Power

- Operating Voltage: 100-264VAC, 50-60 Hertz
- Fuse: 3.5A 250V
- Power Consumption: 290W, 3.66A, pf: .65

Thermal

- Max. Operating Temp.: 104 degrees F (40 degrees C) ambient

Control

- Protocol: USITT DMX-512
- DMX Channels: 4/5/9 or 10-Channels
- Input: 3-pin XLR Male
- Output: 3-pin XLR Female
- Standalone, Master/Slave, Sound Active, Color Preset

Weight & Dimensions

- 35.3" (986 mm) x 3.4" (85 mm) x 9.3 inches (235 mm)
- Weight: 23.2 lbs (10.5 kg)

Warranty

- 2-year limited warranty, does not cover malfunction caused by damage to LEDs.