



Cooler By  
Design™

## Blizzard Lighting, LLC

Phone: 1.866.493.6025

Fax: 1.866.870.0031

Email: [info@blizzardlighting.com](mailto:info@blizzardlighting.com)

Website: <http://www.blizzardlighting.com>

## Taking it to the MAX...

Blizzard's most powerful upgrade yet! The G-Max150 is here! A single-source 150w white LED beam fixture equipped with a 7 colors + open color wheel and 2 gobo wheels with 1 static and 1 rotating, each with 7 gobos + open. With 3 and 8-facet dual prisms, the G-Max150 is sure-fire way to surpass all your competitors.

While having a powerful LED source and amazing optics make this fixture outstanding, it's the G-Max150's options that definitely put this fixture above the rest! With a color wheel that allows for half colors, electronic focus, iris and frost right at your fingertips, it will allow you to have the most robust and versatile fixture for the money. Also, the silent cooling fans are always a plus when lighting theaters and churches.

G-Max's 3 user-selectable DMX modes (21/23/24 channels) allow ease and flexibility in programming, as does its automatic Pan/Tilt position correction. Power connections are via industry standard powerCON® compatible jacks, and DMX 3-pin and 5-pin In/Out jacks + dual quarter-turn "Omega" quick connect type clamp brackets will make this fixture your new heavy hitter!

Finally, G-Max150's built-in automatic programs and sound active in stand-alone mode allow even the most novice user the ability to have pro-type fixtures on their rig... Now is the time to take your setup to the MAX!

### Main Features:

- Single 150w white LED Spot Moving Head
- 16 bit smooth P&T resolution
- Pan: 540° Tilt: 270° with 3-phase motors
- Automatic Pan/Tilt position correction
- User selectable 21/23/24-channel DMX modes
- 7 colors + open color wheel with half-colors
- 2 gobo wheels, 1 static/1 rotating both with 7 gobos + open
- 3/8-facet dual prism with variable speed and direction
- 0-100% linear LED dimmer
- Extremely silent cooling fans
- 3-pin and 5-pin male/female input and outputs
- PowerCon™ compatible AC power In/Out connectors

### Light Source

- 150w White Luminus LED



### Control

- Protocol: USITT DMX-512
- DMX Channels: 21/23/24
- Operating Modes: Standalone, Master/Slave, Auto, Sound

### Active

- Input: 3-pin/5-pin XLR Male
- Output: 3-pin/5-pin XLR Female
- LCD full-color 4-button control panel

### Movement Range

- Pan: 540°
- Tilt: 270°

### Power

- Operating Voltage 90-250VAC, 50-60Hz
- Power Consumption 275W, 2.47a, pf: .99

### Operating Temperature

- Max. Operating Temp.: 104 degrees F (40 degrees C) ambient

### Dimensions

- Length: 15 inches (380 mm)
- Width: 10.2 inches (260 mm)
- Height: 18.9 inches (480 mm)
- Weight: 33 lbs (15 kg)

### Warranty

- 2-year limited warranty, does not cover malfunction caused by damage to LEDs.